



P A I N T I N G

KINGAIR® SEPARATORS

› STANDARD ISO 8573-1:2--1



KAAD

JORC

Separators type STANDARD for installation out of the painting box.
 Removing water **>99,9999%**, residual oil **0,01 mg/m³>91%** and particles up to **0,2 µm>90%**.
 Material aluminium or stainless steel.
 No cartridges.
 Autodrain automatic mechanical type KAAD or level switch automatic JORC (230 V).

Painting gun	Maximal flow up to		KingAir
	[L/min]	[m ³ /h]	
Painting gun standard	300	18	KA300
Painting gun SATA	600	36	KA600
Painting gun standard	900	54	KA900
2 - 3 painting guns or SATA	1500	90	KA1500

› MICROFILTRATION ISO 8573-1:0--0

Microfiltration **KAKIT** for excellent quality painting, for installation out of the painting box.
 Set contains two separators, one carbon filter and one microfilter.
 Oil aerosol **0,0004 mg/m³>99,996%**, particles **0,01 µm**.



KAKIT3-300: for one painting gun

Flow 300 l/min (at 7 bar), recommended replacement of cartridges cca once a year (according air quality).

Material: plastic



KAKIT3-600: for one high pressure painting gun SATA (560 l/min) or two standard painting guns

Flow 600 l/min (at 7 bar), recommended replacement of cartridges cca once a year (according air quality).

Material: aluminium